SAFETY DATA SHEET

SECTION 1: Identification

Product Name: FORM #852 525 CLEAR A COMP Product Code: 852 525 CLEAR A

Trade Name: 525 PART A EMERGENCY PHONE: PERS 1-800-633-8253

MANUFACTURER:

Madewell Products Corporation

7561 Industrial Court Alpharetta GA 30004 Phone: (770) 475-8199

SECTION 2: Hazard(s) Identification

GHS Ratings:

Flammable liquid 2 Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosion/irritation 2 Reversible adverse effects in dermal tissue, Draize score: >=

2.3 < 4.0 or persistent inflammation

Serious eye damage/eye 2A Eye irritant: Subcategory 2A, Reversible in 21 days

irritation

Reproductive toxicity 1B Presumed, Based on experimental animals

GHS Hazards

H225 Highly flammable liquid and vapour

H315 Causes skin irritation

H319 Causes serious eye irritation

H360 May damage fertility or the unborn child

GHS Precautions

P501

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light//equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P264	Wash hands thoroughly after handling
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P321	Specific treatment (see instructions on this label)
P362	Take off contaminated clothing and wash before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact
	lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	If eye irritation persists, get medical advice/attention
P370+P378	In case of fire: Use for extinction
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool

SDS for: 852 525 CLEAR A Page 1 of 7

Dispose of contents/container to ...

Signal Word: Danger







SECTION 3: Composition/Information on Ingredients				
Chemical Name	CAS number	Weight Concer		
KETONE	70.02.2	40.000/ 0		

Chemical Name	CAS number	Weight Concentration %
METHYL ETHYL KETONE	78-93-3	10.00% - 20.00%
1-METHOXY-2-PROPANOL	108-65-6	5.00% - 10.00%
1-methoxypropan-2-ol	107-98-2	1.00% - 5.00%

SECTION 4: First Aid Measures

INHALATION: Move person to fresh air and keep at rest in a position for breathing: if breathing is irregular, provide artificial respiration; if there are breathing difficulties, administer oxygen; get medical attention.

EYE CONTACT: Bathe the eye with running water for at least 15 minutes, lifting upper and lower eyelids. SKIN CONTACT: Rinse immediately with plenty of water: remove contaminated clothing; wash thoroughly with

soap and waer for at least 15 minutes. If irritation, rash or other adverse effects develop, get medical attention immediately.

INGESTION: Do NOT induce vomiting unless advised by a physician. Rinse out mouth with water. Call nearest Poison Control Center or physician immediately.

Most important symptoms and effects, both acute and delayed. Harmful in contact with skin, if swallowed or inhaled; can cause severe skin burns and eye damage; may cause an allergic skin reaction.

Indication of any immediate medical attention and special treatment needed.

Treat symptomatically.

Eve wash stations and emergency showers should be available.

SECTION 5: Fire Fighting Measures

Flash Point: 10 C (50 F)

UEL: 1.0% LEL: 13.0%

Extinguishing Media

Carbon dioxide, alcohol resistant foam, dry chemical, water fog; use water spray to cool fire-exposed containers.

Unsuitable Extinguishing Media

High volume water jet

Special hazards arising from the substance or misture

Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flash back. Vapor concentrations in enclosed areas my ignite explosively. Empty containers may contain ignitable vapors. Exposure to decomposition products may be harmful to health; combustion products may include but are not limited to: carbon monoxide carbon dioxide, nitrogen oxides; the formation of hydrocarbon fragments is possible in the initial stages of fire; smoke may contain particles of the orginal material as well. Prevent fire-fighting waters from entering sewer or waterways.

Polymerization will take place under fire conditions. If polymerization occurs in a closed container, there is a possiblity it will rupture violently. Cool storage container with water, if exposed to fire.

Hazardous combustion products: Hydrocarbons

carbon dioxide and carbon monoxide

toxic fumes

Advice for fire fighters: Use protective fire fighting clothing and positive pressure self contained breathing apparatus to protect against potential harmful and/or irritating fumes. Do not use high pressure water jet as this may spread the area of the fire.

Fire Equipment: Wear self-contained breathing apparatus

SDS for: 852 525 CLEAR A Page 2 of 7

SECTION 6: Accidental Release Measures

Personal precautions

Isolate area: ensure adequate ventilation; remove all sources of ignition; use appropriate personal protection equipment. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Halt the flow of materials as soon as practical using appropriate barriers; turn containers leak-side up to stop the escape of liquid. Prevent contamination of soil and water. Prevent from spreading or entering into drains, ditches, waterways by using sand, earth or appropriate barriers.

Methods and material for containment and clean up

Soak up with sand, earth, diatomaceous earth or other suitable inert absorbent materials; collect into suitable waste disposal containers. Reuse uncontaminated material when possible. Wsh spillage site with large amounts of water, Dispose of in accordance with applicable local and federal environmental control laws and regulations.

SECTION 7: Handling and Storage

Precautions for safe handling

Do not use sodium nitrite or other nitrosating agents in formulations containing this product. Avoid formation of aerosol. Ensure adequate ventilation. Prevent inhalation of vapor, ingestion, and contact with skin, eyes and clothing. Keep containers closed when not is use. Precautions apply to empty containers as well. Do not eat, drink, or smoke in the work area. Wash thoroughly after handling. Personal protective equipment must be worn during maintenance or repair of mixers, reactors or other equipment containing the material.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry area with adequate ventilation. Do not store with strong oxidizing agents. Keep container tightly closed. Conatainers which are opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8: Exposure Controls/Personal Protection						
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits			
METHYL ETHYL KETONE 78-93-3	Not Established	Not Established	Not Established			
1-METHOXY-2-PROPANOL 108-65-6	Not Established	Not Established	Not Established			
1-methoxypropan-2-ol 107-98-2	Not Established	Not Established	Not Established			

Engineering controls:

Follow good industrial workplace practices; do not eat, drink or smoke while handling; wash hands before breaks and at end of workshift; follow recommendations in this SDS.

Environmental exposure controls

Observe all precautions to prevent contamination of soil and waterways.

Eye/face protection

Wear tight-fitting chemical safety goggles and/or face shield to prevent eye contact.

Skin protection

Wear impervious clothing as necessary to protect against product contact. Necessity for boots, apron, face shield, etc. will be dependent on any hazards presented in the work process.

Respiratory protection

Respiratory protection is required wherever exposure limits are exceeded; use a NIOSH approved organic vapor

SDS for: 852 525 CLEAR A Page 3 of 7

cartridge respirator following the guidelines of an established respiratory protetion program in compliance whith 29CFR1910.134

Hand protection

Use suitable impervious neoprene or nitrile rubber gloves. When prolonged or frquently repeated contact may occur, glove material should have a breakthrough time that exceeds 480 minutes; when only brief contact is expected, a glove with a lesser breakthrough rating may be suitable.

Other protective equipment

The type and degree of personal protective equipment appropriate will depend on the specific work operation. Eye wash stations and emergency shower should be available. Inspect and replace personal protective equipment at regular intervals; use professional care in their selection, use and care

SECTION 9: Physical and Chemical Properties

PHYSICAL STATE: LIQUID pH: No data available

RELATIVE EVAPORATION RATE: No data available

MELTING POINT: Not determined BOILING POINT: Not determined FLASH POINT: 10C 80F

AUTO IGNITION TEMPERATURE: Not determined **DECOMPOSITION TEMPERATURE:** Not determined

VAPOUR PRESSURE: Not determined RELATIVE VAPOUR DENSITY: 3.6

DENSITY: 8.29LBS/GAL **SOLUBILITY:** Insoluble

EXPLOSIVE PROPERTIES: Not determined **OXIDISING PROPERTIES:** Not determined

Boiling Range 80 to 146 °C

SECTION 10: STABILITY AND REACTIVITY

STABLE

Reactivity: No dangerous reaction is known under normal use and storage conditions.

Stability: Stable under normal use and storage conditions.

Possibility of hazardous reactions: Hazardous polymerisation may occur. Vapours may form explosive mixture with air. This product does not present a dust explosion hazard as delivered. However, fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source, is a potential dust explosion hazard.

Conditions to avoid: Heat, flames, and sparks. Excessive heat. Direct sources of heat. Exposure to air and sunlight.

Incompatible materials: Acids, aluminum, aluminum chloride, amines, bases, copper, copper alloys, halogens, iron chloride, metal salts, oxidizing agents, peroxides.

Hazardous decomposition products: Thermal decomposition will generate carbon monoxide, carbon dioxide and nitrogen oxides.

Hazardous polymerization will not occur.

SECTION 11: Toxicological Information

SDS for: 852 525 CLEAR A Page 4 of 7

Information on toxicological effects

Acute Oral Toxicity: LD50(rat):> 2000 mg/kg
Acute Dermal Toxicity: LD50(rabbit): >2000 mg/kg

Acute Inhalation Toxicity: LD50 (Rat): 1.8 mg/l, 2770 ppm Exposure time: 4h Test atmosphere: vapour. No

abserved adverse effect level (Humans): 100 ppm Exposure time 7 h Test atmosphere: vapour

Skin Corrosion/Irritation: Causes skin irritation

Serious Eye Damage/Irritation: Causes serious eye irritation

Skin Sensitization): Not classified based on available information. May cause an allergic skin reaction.

Germ cell Mutagenicity: Not classified as mutagenic.

Caracinogenicity: Not classified as carcinogenic. Not listed by OSHA/NTP/IARC.

Reproductive Toxicity: Not classified as reproductive toxin.

Specific Target Organ Toxicity - single exposure: Product not classified based on available data. **Specific Target Organ Toxicity - repated exposure:** Product not classified based on available data.

Aspiration Hazard: Possible aspiration hazard alkaline).

Potential Health Effects:

Skin Contact: Corrosive; harmful in contact with skin; may cause itching, reddening, inflammation. May cause severe burns, blistering and skin damage; may cause an allergic reaction.

Eye Contact: Contact with vapors or liquid may cause tearing, blurred vision, severe irritation, possible chemical burns and corneal injury.

Ingestion: Harmful if swallowed; can cause severe and permanent damage to mouth, throat and stomach, may cause injury to the liver and kidneys.

Inhalation: harmful if inhaled; can cause moderate to severe irritation of the respiratory tract.

Chronic Health Effects:

May cause sensitization by contact. Prolonged skin contact may cause irritation, rash, burns or dermatitis; repeated overexposure to vapors and/or liquidmay injure the liver, kidneys and respiratory system. May aggravate individuals sensitized to amines.

Mixture Toxicity
Component Toxicity

Effects of Overexposure

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>
None

N/A

SECTION 12 - ECOLOGICAL INFORMATION

Toxicity

Acute/prolonged toxicity to fish:LC50(Lepomis macrochirus)(96-hr): 4.02 mg/l

Acute/prolonged toxicity to aquatic invertebrates: EC50 (Daphnia magna)(48-hr): 35 mg/l (ATE)

Acute/prolonged toxicity to aquatic plants: EC50(72-hr): >50 mg/l (ATE)

Toxicity to bacteria, to soil dwelling organisms and to terrestrial plants: No data available

Chronic toxicity to aquatic organisms: No data available General effect: Harmful to aquatic life with long lasting effects.

Persistence and degradability: Not expected to be readily biodegradable

Bioaccumulative potential: One or more products components has a low potential to bioaccumlate

Mobility in soil: No data available; do not allow product to enter soil/subsoil

SDS for: 852 525 CLEAR A Page 5 of 7

Results of PBT and vPvB assessment (EC reg. 453/2010): Product not classified as Persistent, Bioaccumulative and Toxic

Product not classified as very Persistent or very Bioaccumulative **Other advers effects:** No other adverse effects ae identified

Component Ecotoxicity

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal: Do not dump to ground, sewers or watercourses. Incinerate or otherwise dispose of in compliance with all applicable federal, state and local environmental control laws and regulations. Waste characterization according to RCRA guidelines and compliance with applicable laws are the responsibility solely of the waste generator. Send waste to a licensed waste management company.

Container Disposal: Containers should be drained of all residual product prior to disposal. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Do not burn, or use a cutting torch on the empty drum.

SECTION 14 - TRANSPORT INFORMATION

DOT, IMDG, AND IATA Proper Shipping Description: UN1993, FLAMMABLE LIQUIDS NOS(CONTAINS METHYL ETHYL KETONE),3,PGIII

Agency Proper Shipping Name

UN Number Packing Grou Hazard Class

SECTION 15 - REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Title III Section 311/312 (40CFR370): Reactivity hazard, acute health hazard, fire hazard, chronic health hazard.

SARA Title III Section 313 (40CFR372): Styrene 100-42-5 10-20%

CERCLA Status (40CFR302): Styrene 100-42-5 Component RQ 1000 lbs.

OSHA/NTP/IARC Carcinogen Status: WARNING This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. Benzene 71-43-2

TSCA Inventory Status: Reported/included

Chemicals known to the state of California to cause cancer or reproductive toxicity: Benzene 71-43-2

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

Country Regulation All Components Listed

SECTION 16 - OTHER INFORMATION

HMIS ratings: Health: 2*

Flammability:3
Physical hazard: 2

Hazardous Material Information System (HMIS)

SDS for: 852 525 CLEAR A Page 6 of 7



HMIS & NFPA Hazard Rating Legend

= Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

THE INFORMATION OR RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON STANDARD PRODUCT AND ARE PROPRIETARY AND FURNISHED SOLELY FOR THE USE OF OUR CUSTOMERS. THIS INFORMATION IS PROVIDED IN GOOD FAITH AND BELIEVED TO BE TRUE AND ACCURATE AS OF THE DATE SHOWN BELOW; HOWEVER, SINCE WE HAVE NO CONTROL OVER THE USE CONDITIONS OR PRODUCTION PROCESSES OF PARTIES USING THIS PRODUCT, MADEWELL PRODUCTS CORPORATION CANNOT ACCEPT RESPONSIBILITY FOR LOSS, INJURY OR OTHER DAMAGES RESULTING FROM THE USE OF THE PRODUCTS OR THIS OR ANY OTHER INFORMATION PROVIDED BY US. THEREFORE, NO GUARANTEES OF ANY KIND, EXPRESSED OR IMPLIED, ARE MADE BY MADEWELL PRODUCTS CORPORATION WITH REGARD TO ANY OF THEIR PRODUCTS. USERS ARE ADVISED TO PERFORM THEIR OWN TESTS AND HAZARD ASSESSMENTS TO DETERMINE THE SAFETY. SUITABILITY AND RELEVANCE OF APPLICABLE LAW TO THE PRODUCTS AS IT IS TO BE USED BY THEM.

Reviewer Revision

Date Prepared: 3/27/2025

SDS for: 852 525 CLEAR A Page 7 of 7

Printed: 3/27/2025 at 12:27:27PM