# **SAFETY DATA SHEET**

# **SECTION 1: Identification**

Product Name: PROD NO 762 DS5 B BLUE/GRAY Product Code: 762 DS5 B BLUE/GRAY

Trade Name: MAINSTAY DS-5 B

Trade Name: MAINSTAY DS-5 PART B EMERGENCY PHONE: PERS 1-800-633-8253

MANUFACTURER:

**Madewell Products Corporation** 

7561 Industrial Court Alpharetta GA 30004 Phone: (770) 475-8199

# SECTION 2: Hazard(s) Identification

# **GHS Ratings:**

| Flammable liquid            | 4  | Flash point $\geq$ 60°C (140°F) and $\leq$ 93°C (200°F)     |
|-----------------------------|----|---|
| Acute Toxicity - Inhalation | 3  | Gases>500+<=2500ppm, Vapors>2+<=10mg/l,                     |
|                             |    | Dusts&mists>0.5+<=1mg/l                                     |
| Skin corrosion/irritation   | 1A | Destruction of dermal tissue: Exposure < 3 min. Observation |
|                             |    | < 1 hour, visible necrosis in at least one animal           |
| Serious eye damage/eye      | 1  | Serious eye damage: Irreversible damage 21 days after       |
| irritation                  |    | exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5  |
| Carcinogenicity             | 1A | Known Human Carcinogen Based on human evidence              |

# **GHS Hazards**

| H227 | Combustible liquid                      |
|------|---|
| H314 | Causes severe skin burns and eye damage |
| H318 | Causes serious eye damage               |
| H331 | Toxic if inhaled                        |
| H350 | May cause cancer                        |
|      |   |

# **GHS Precautions**

SDS for: 762 DS5 B BLUE/GRAY

| P201           | Obtain special instructions before use   |
|----------------|--|
| P202           | Do not handle until all safety precautions have been read and understood           |
| P210           | Keep away from heat/sparks/open flames/hot surfaces – No smoking                   |
| P235           | Keep cool  |
| P260           | Do not breathe dust/fume/gas/mist/vapours/spray                                    |
| P261           | Avoid breathing dust/fume/gas/mist/vapours/spray                                   |
| P264           | Wash hands thoroughly after handling   |
| P271           | Use only outdoors or in a well-ventilated area                                     |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection          |
| P281           | Use personal protective equipment as required                                      |
| P310           | Immediately call a POISON CENTER or doctor/physician                               |
| P311           | Call a POISON CENTER or doctor/physician   |
| P321           | Specific treatment (see instructions on this label)                                |
| P363           | Wash contaminated clothing before reuse  |
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting                                  |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse |
|                | skin with water/shower   |
| P304+P340      | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable  |
|                | for breathing  |
| P305+P351+P338 | IF IN EYES: Rinse continuously with water for several minutes. Remove contact      |
|                | lenses if present and easy to do – continue rinsing                                |

P308+P313 IF exposed or concerned: Get medical advice/attention

P370+P378 In case of fire: Use ... for extinction

P405 Store locked up

P403+P233 Store in a well ventilated place. Keep container tightly closed

P403+P235 Store in a well ventilated place. Keep cool

P501 Dispose of contents/container to ...

#### Signal Word: Danger



| SECTION 3: Composition/Information on Ingredients |            |                        |  |  |  |
|---|------------|------------------------|--|--|--|
| Chemical Name                                     | CAS number | Weight Concentration % |  |  |  |
| QUARTZ  | 14808-60-7 | 30.00% - 40.00%        |  |  |  |
| TITANIUM DIOXIDE                                  | 13463-67-7 | 20.00% - 30.00%        |  |  |  |
| POLYOXYPROPYLENE DIAMINE                          | 9046-10-0  | 10.00% - 20.00%        |  |  |  |

#### **SECTION 4: First Aid Measures**

**INHALATION:** Move person to fresh air and keep at rest in a position for breathing: if breathing is irregular, provide artificial respiration; if three are breathing difficulties, administer oxygen; get medical attention.

**EYE CONTACT:** Bathe the eye with running water for at least 15 minutes, lifting upper and lower eyelids. Get medical attention immediately.

**SKIN CONTACT:** Rinse immediately with plenty of water: remove contaminated clothing; wash thoroughly with soap and waer for at least 15 minutes. If irritation, rash or other adverse effects develop, get medical attention immediately.

**INGESTION:** Do NOT induce vomiting unless advised by a physician. Rinse out mouth with water. Call nearest Poison Control Center or physician immediately.

**Most important symptoms and effects, both acute and delayed.** Harmful in contact with skin, if swallowed or inhaled; can cause severe skin burns and eye damage; may cause an allergic skin reaction.

# Indication of any immediate medical attention and special treatment needed.

Treat symptomatically.

Eye wash stations and emergency showers should be available.

#### **SECTION 5: Fire Fighting Measures**

Flash Point: 93 C (199 F)

LEL: 1.0% UEL: 5.0%

# **Extinguishing Media**

Carbon dioxide, alcohol resistant foam, dry chemical, water fog; use water spray to cool fire-exposed containers.

# Special hazards arising from the substance or misture

Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flash back. Vapor concentrations in enclosed areas my ignite explosively. Empty containers may contain ignitable vapors. Exposure to decomposition products may be harmful to health; combustion products may include but are not limited to: carbon monoxide carbon dioxide, nitrogen oxides; the formation of hydrocarbon fragments is possible in the initial stages of fire; smoke may contain particles of the orginal material as well. Prevent fire-fighting waters from entering sewer or waterways.

**Advice for fire fighters:** Use protective fire fighting clothing and positive pressure self contained breathing apparatus to protect against potential harmful and/or irritating fumes. Do not use high pressure water jet as this

SDS for: 762 DS5 B BLUE/GRAY Page 2 of 7

#### SECTION 6: Accidental Release Measures

## **Personal precautions**

Isolate area: ensure adequate ventilation; remove all sources of ignition; use appropriate personal protection equipment; avoid breathing mist, vapors, spray; avoid contact with skin, eyes and clothing; keep unnecessary and unprotected personnel from entering the involved area.

#### **Environmental precautions**

Halt the flow of materials as soon as practical using appropriate barriers; turn containers leak-side up to stop the escape of liquid. Prevent contamination of soil and water. Prevent from spreading or entering into drains, ditches, waterways by using sand, earth or appropriate barriers.

# Methods and material for containment and clean up

Soak up with sand, earth, diatomaceous earth or other suitable inert absorbent materials; collect into suitable waste disposal containers. Reuse uncontaminated material when possible. Wsh spillage site with large amounts of water, Dispose of in accordance with applicable local and federal environmental control laws and regulations.

## **SECTION 7: Handling and Storage**

# Precautions for safe handling

Ensure adequate ventilation. Prevent inhalation of vapor, ingestion, and contact with skin, eyes and clothing. Keep containers closed when not is use. Precautions apply to empty containers as well. Do not eat, drink, or smoke in the work area. Wash thoroughly after handling. Personal protective equipment must be worn during maintenance or repair of mixers, reactors or other equipment containing the material.

## Conditions for safe storage, including any incompatibilities

Store in a cool, dry area with adequate ventilation. Do not store with strong oxidizing agents.

| SECTION 8: Exposure Controls/Personal Protection |                      |                                  |                       |  |  |  |
|--|----------------------|----------------------------------|-----------------------|--|--|--|
| Chemical Name / CAS No.                          | OSHA Exposure Limits | ACGIH Exposure Limits            | Other Exposure Limits |  |  |  |
| QUARTZ<br>14808-60-7                             | .1MG/M3              | .025MG/M3 RESPIRABLE<br>FRACTION | Not Established       |  |  |  |
| TITANIUM DIOXIDE<br>13463-67-7                   | TWA 15 MG/M3         | TWA 10MG/M3                      | Not Established       |  |  |  |
| POLYOXYPROPYLENE<br>DIAMINE<br>9046-10-0         | Not Established      | Not Established                  | Not Established       |  |  |  |

# **Engineering controls:**

Follow good industrial workplace practices; do not eat, drink or smoke while handling; wash hands before breaks and at end of workshift; follow recommendations in this SDS.

## **Environmental exposure controls**

Observe all precautions to prevent contamination of soil and waterways.

#### Eye/face protection

Wear tight-fitting chemical safety goggles and/or face shield to prevent eye contact.

## Skin protection

Wear impervious clothing as necessary to protect against product contact. Necessity for boots, apron, face shield, etc. will be dependent on any hazards presented in the work process.

SDS for: 762 DS5 B BLUE/GRAY Page 3 of 7

## Respiratory protection

Respiratory protection is required wherever exposure limits are exceeded; use a NIOSH approved organic vapor cartridge respirator following the guidelines of an established respiratory protetion program in compliance whith 29CFR1910.134

#### Hand protection

Use suitable impervious neoprene or nitrile rubber gloves. When prolonged or frquently repeated contact may occur, glove material should have a breakthrough time that exceeds 480 minutes; when only brief contact is expected, a glove with a lesser breakthrough rating may be suitable.

#### Other protective equipment

The type and degree of personal protective equipment appropriate will depend on the specific work operation. Eye wash stations and emergency shower should be available. Inspect and replace personal protective equipment at regular intervals; use professional care in their selection, use and care

# **SECTION 9: Physical and Chemical Properties**

**PHYSICAL STATE: LIQUID** 

pH: Alkaline

RELATIVE EVAPORATION RATE: <1 MELTING POINT: Not determined BOILING POINT: Not determined FLASH POINT: >93C (>200F) (cc)

**AUTO IGNITION TEMPERATURE:** Not determined **DECOMPOSITION TEMPERATURE:** Not determined

VAPOUR PRESSURE: Not determined RELATIVE VAPOUR DENSITY: >1

**SPECIFIC GRAVITY:** 1.03

**SOLUBILITY:** Nil

**EXPLOSIVE PROPERTIES:** Not determined **OXIDISING PROPERTIES:** Not determined

Boiling Range 232 to 5000 °C

# **SECTION 10: STABILITY AND REACTIVITY**

### STABLE

Reactivity: No dangerous reaction is known under normal use and storage conditions.

**Stability:** Stable under normal use and storage conditions.

**Possibility of hazardous reactions:** Mixtures with strongly acidic and strongly alkaline materials may produce an exothermic reaction.

Conditions to avoid: Avoid elevated temperatures and sources of ignition.

**Incompatible materials:** Acids, oxidizing agents, epoxies, isocyanates.

**Hazardous decomposition products:** Thermal decomposition will generate caron monoxide, carbon dioxide and nitrogen oxides.

Hazardous polymerization will not occur.

**SECTION 11: Toxicological Information** 

SDS for: 762 DS5 B BLUE/GRAY Page 4 of 7

Information on toxicological effects

Acute Oral Toxicity: LD50(rat): 1300 mg/kg (ATE)
Acute Dermal Toxicity: LD50(rabbit): 1940 mg/kg (ATE)

Acute Inhalation Toxicity: >5.01mg/l

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

Serious Eye Damage/Irritation: Causes serious eye damage. Skin Sensitization (guinea pig): May cause an allergic skin reaction.

Germ cell Mutagenicity: Not classified as mutagenic.

Caracinogenicity: Not classified as carcinogenic. Not listed by OSHA/NTP/IARC.

Reproductive Toxicity: Not classified as reproductive toxin.

**Specific Target Organ Toxicity - single exposure:** Product not classified based on available data. **Specific Target Organ Toxicity - repated exposure:** Product not classified based on available data.

Aspiration Hazard: Possible aspiration hazard alkaline).

#### **Potential Health Effects:**

**Skin Contact:** Corrosive; harmful in contact with skin; may cause itching, reddening, inflammation. May cause severe burns, blistering and skin damage; may cause an allergic reaction.

**Eye Contact:** Contact with vapors or liquid may cause tearing, blurred vision, severe irritation, possible chemical burns and corneal injury.

**Ingestion:** Harmful if swallowed; can cause severe and permanent damage to mouth, throat and stomach, may cause injury to the liver and kidneys.

Inhalation: harmful if inhaled; can cause moderate to severe irritation of the respiratory tract.

#### **Chronic Health Effects:**

May cause sensitization by contact. Prolonged skin contact may cause irritation, rash, burns or dermatitis; repeated overexposure to vapors and/or liquidmay injure the liver, kidneys and respiratory system. May aggravate individuals sensitized to amines.

#### **Mixture Toxicity**

Inhalation Toxicity LC50: 4mg/L

# **Component Toxicity**

9046-10-0 POLYOXYPROPYLENE DIAMINE

Oral LD50: 2,885 mg/kg (RAT) Dermal LD50: 2,980 mg/kg (RABBIT) Inhalation LC50: 1

mg/L (RAT)

#### **Effects of Overexposure**

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u> 14808-60-7 QUARTZ 30% - 40% QUARTZ:

#### **SECTION 12 - ECOLOGICAL INFORMATION**

# **Toxicity**

Acute/prolonged toxicity to fish:LC50(Lepomis macrochirus)(96-hr): 16 mg/l (ATE)

Acute/prolonged toxicity to aquatic invertebrates: EC50 (Daphnia magna)(48-hr): 35 mg/l (ATE)

Acute/prolonged toxicity to aquatic plants: EC50 (Green algae)(72-hr): >50 mg/l (ATE)

Toxicity to bacteria, to soil dwelling organisms and to terrestrial plants: No data available

Chronic toxicity to aquatic organisms: No data available General effect: Harmful to aquatic life with long lasting effects.

Persistence and degradability: Not expected to be readily biodegradable

SDS for: 762 DS5 B BLUE/GRAY Page 5 of 7

Bioaccumulative potential: One or more products components has a low potential to bioaccumlate

Mobility in soil: No data available; do not allow product to enter soil/subsoil

Results of PBT and vPvB assessment (EC reg. 453/2010): Product not classified as Persistent, Bioaccumulative

and Toxic

Product not classified as very Persistent or very Bioaccumulative Other advers effects: No other adverse effects ae identified

**Component Ecotoxicity** 

# **SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal: Do not dump to ground, sewers or watercourses. Incinerate or otherwise dispose of in compliance with all applicable federal, state and local environmental control laws and regulations. Waste characterization according to RCRA guidelines and compliance with applicable laws are the responsibility solely of the waste generator.

Container Disposal: Containers should be drained of all residual product prior to disposal.

#### **SECTION 14 - TRANSPORT INFORMATION**

DOT, IMDG, AND IATA Proper Shipping Description: UN1760, Corrosive Liquids NOS (contains polyoxypropylene and modified amine) Hazard Class 8 PG III

Agency **Proper Shipping Name**  UN Number Packing Grou Hazard Class

#### **SECTION 15 - REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Title III Section 311/312 (40CFR370): Acute health hazard SARA Title III Section 313 (40CFR372): No reportable components

CERCLA Status (40CFR302): No reportable components

RCRA Status (40CFR261): Not listed

OSHA/NTP/IARC Carcinogen Status: Not listed TSCA Inventory Status: Reported/included Canadian DSL Status: Rported/included Canadian WHMIS Status: D2B,E

Chemicals known to the state of California to cause cancer or reproductive toxicity: None known to be in the

product at levels requiring a warning

Chemical safety assessment: Not available

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

14808-60-7 QUARTZ 30 - 40% REPRODUCTIVE



**WARNING:** This product can expose you to CARBON BLACK, which is known to the State of California to cause cancer, and QUARTZ, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

All Components Listed Country Regulation

#### **SECTION 16 - OTHER INFORMATION**

**HMIS** ratings:

Health: 3 Flammability:1

SDS for: 762 DS5 B BLUE/GRAY Page 6 of 7

## **Hazardous Material Information System (HMIS)**



HMIS & NFPA Hazard Rating Legend

\* = Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

THE INFORMATION OR RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON STANDARD PRODUCT AND ARE PROPRIETARY AND FURNISHED SOLELY FOR THE USE OF OUR CUSTOMERS. THIS INFORMATION IS PROVIDED IN GOOD FAITH AND BELIEVED TO BE TRUE AND ACCURATE AS OF THE DATE SHOWN BELOW; HOWEVER, SINCE WE HAVE NO CONTROL OVER THE USE CONDITIONS OR PRODUCTION PROCESSES OF PARTIES USING THIS PRODUCT, MADEWELL PRODUCTS CORPORATION CANNOT ACCEPT RESPONSIBILITY FOR LOSS, INJURY OR OTHER DAMAGES RESULTING FROM THE USE OF THE PRODUCTS OR THIS OR ANY OTHER INFORMATION PROVIDED BY US. THEREFORE, NO GUARANTEES OF ANY KIND, EXPRESSED OR IMPLIED, ARE MADE BY MADEWELL PRODUCTS CORPORATION WITH REGARD TO ANY OF THEIR PRODUCTS. USERS ARE ADVISED TO PERFORM THEIR OWN TESTS AND HAZARD ASSESSMENTS TO DETERMINE THE SAFETY, SUITABILITY AND RELEVANCE OF APPLICABLE LAW TO THE PRODUCTS AS IT IS TO BE USED BY THEM.

Reviewer Revision

Date Prepared: 3/27/2025

SDS for: 762 DS5 B BLUE/GRAY